NSN 5305-00-005-8297

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-005-8297 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.317 inches **Fastener Length:** Between 0.635 inches and 0.682 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.329 inches and 0.337 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c **Countersink Angle:** Between 99.5 degrees and 100.5 degrees Surface Finish: 32.0 microinches grip Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-005-8297

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0