
Socket Head Cap Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.672 inches and 0.766 inches Fastener Length: Between 0.734 inches and 0.766 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches Hole Diameter: 0.036 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Hole Configuration Style: Round Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium

NSN 5305-00-005-9071

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0