

View Online at <https://aerobasegroup.com/nsn/5305-00-006-0521>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.240 inches

**Fastener Length:**

0.560 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**First Diameter From Head:**

0.095 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.320 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

60 degree cone point

**Material:**

Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316 or steel comp 310 or steel comp 309 or steel comp 305 or steel comp 304 or steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

**Material Specification:**

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-s-763 federal specification 7th material response or qq-s-763 federal specification 8th material response or qq-s-763 federal specification 9th material response or qq-s-763 federal specification 10th material response or qq-s-763 federal specification 11th material response or 66 assn standard 12th material response or 66 assn standard 13th material response or 66 assn standard 14th material response or 66 assn standard 15th material response or 66 assn standard 16th material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

**Demilitarization:**

No

**Fiig:**

A003b0