## NSN 5305-00-006-2267

Socket Head Cap Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-00-006-2267  |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.573 inches and 0.641 inches  |
| Fastener Length:   |
| Between 0.609 inches and 0.641 inches  |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| Between 0.134 inches and 0.140 inches  |
| Head Height:   |
| Between 0.083 inches and 0.086 inches  |
| Internal Drive Style:  |
| Hexagon  |
| Thread Diameter:   |
| 0.086 inches   |
| Width Across Flats:  |
| Between 0.078 inches and 0.079 inches  |
| Thready Qty Per Inch (tpi):  |
| 56   |
| Min. Tensile Strength (psi):   |
| 80000 pounds per square inch   |
| Hardness Rating:   |
| 80.0 rockwell b  |
| Minimum Yield Strength:  |
| 30000 pounds per square inch   |
| Material:  |
| Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel  |
| Material Specification:  |
| 66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 6 |
| federal standard 4th material response or 66 federal standard 5th material response or astm-a493 aisi xm-7 assn standard 6th material    |
| response   |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |
| Unc  |
| Specification Data:  |
| 90205 pag1252 professional/industrial association standard   |

N/a

Shelf Life:

## NSN 5305-00-006-2267

Socket Head Cap Screw - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A003b0