NSN 5305-00-006-2296

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-006-2296

•
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.246 inches and 0.323 inches
Fastener Length:
Between 1.136 inches and 1.183 inches
Head Style:
Pan
Head Diameter:
Between 0.258 inches and 0.276 inches
Head Height:
Between 0.074 inches and 0.086 inches
Grip Diameter:
Between 0.1365 inches and 0.1375 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.138 inches
Grip Length:
Between 0.860 inches and 0.890 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unc
Specification Data:
76823-51b219 manufacturers standard
Shelf Life:

N/a

NSN 5305-00-006-2296

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0