

View Online at <https://aerobasegroup.com/nsn/5305-00-006-2409>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.188 inches

**Fastener Length:**

Between 2.156 inches and 2.250 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.226 inches and 0.243 inches

**Width Between Flats:**

Between 0.551 inches and 0.563 inches

**Shank Unthreaded Hole Diameter:**

0.105 inches first hole and 0.113 inches first hole

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

120000 pounds per square inch

**Hardness Rating:**

25.0 rockwell c and 34.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.990 inches first hole and 2.104 inches first hole

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel

**Material Specification:**

Sae gr 5 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type and 10p style and 5 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0