## NSN 5305-00-006-4246

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-006-4246 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** 0.750 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.380 inches and 0.500 inches **Head Height:** 0.188 inches **First Diameter From Head:** Between 0.266 inches and 0.326 inches **Second Diameter From Head:** Between 0.140 inches and 0.150 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.562 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material: Steel comp 303 **Material Specification:** Mil-s-7720 military specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

-

## NSN 5305-00-006-4246

Externally Relieved Body Screw - Page 2 of 2



_		••	• •				
n	em	ш	112	riz	<b>2</b> †1	n	٠.

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7720 spec.