

View Online at <https://aerobasegroup.com/nsn/5305-00-006-4867>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.413 inches and 1.531 inches

Fastener Length:

Between 1.484 inches and 1.531 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.365 inches and 0.375 inches

Head Height:

Between 0.244 inches and 0.250 inches

Shank Unthreaded Hole Diameter:

0.046 inches first hole and 0.050 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

Between 0.187 inches and 0.190 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.380 inches first hole and 1.447 inches first hole

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0