NSN 5305-00-006-8283

Tapping Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-006-8283

Fastener Length:
Between 0.953 inches and 1.000 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.452 inches and 0.507 inches
Internal Drive Style:
Cross recess type 1
Nonmachine Thread Style:
Thru slot (type d) or double flute (type f) or through slot (type 6) or wide flute (type t)
Countersink Angle:
Between 80.0 degrees and 82.0 degrees
Nonmachine Thread Diameter:
0.250 inches
Material:
Steel comp 4032
Material Specification:
66 federal standard all material responses
Surface Treatment:
Surface Treatment: Passivate
Passivate
Passivate Surface Treatment Specification:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: