

View Online at <https://aerobasegroup.com/nsn/5305-00-006-8410>

Fastener Length:

Between 0.820 inches and 0.880 inches

Head Style:

Hexagon extended washer

Head Height:

Between 0.263 inches and 0.265 inches

Width Between Flats:

Between 0.489 inches and 0.500 inches

Extended Washer Diameter:

Between 0.624 inches and 0.676 inches

Extended Washer Thickness:

Between 0.035 inches and 0.055 inches

Internal Drive Style:

W/o internal drive

Features Provided:

Casehardened

Hardness Rating:

83.0 rockwell superficial 15-n

Nonmachine Thread Style:

Blunt (sf) or blunt (type sw) or blunt (type tt)

Nonmachine Thread Diameter:

0.312 inches

Special Features:

Triangle /taptite/ shape threads

Material:

Steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022

Material Specification:

Qq-w-405 federal specification all material responses

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Mil-p-16232 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-p-16232 spec.