NSN 5305-00-007-0189

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-0189 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.125 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.090 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.344 inches and 0.375 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Hp-4-169 fscm 82577 mfr ref single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-007-0189

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0