## NSN 5305-00-007-0289

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-0289 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.102 inches and 0.111 inches **Fastener Length:** Between 0.217 inches and 0.221 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.079 inches and 0.081 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.110 inches and 0.115 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

## NSN 5305-00-007-0289

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0