Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-0289

7	Thread Class:
	2a
	Fhread Direction:
	Right-hand
	Thread Length:
	Between 0.102 inches and 0.111 inches
	Fastener Length:
	Between 0.217 inches and 0.221 inches
	lead Style:
	Pan no. 2
	lead Diameter:
	Between 0.205 inches and 0.219 inches
	lead Height:
	Between 0.070 inches and 0.080 inches
I	First Diameter From Head:
E	Between 0.079 inches and 0.081 inches
I	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
	Between 0.110 inches and 0.115 inches
I	nternal Drive Style:
	Dffset cruciform (torque set)
	Thread Diameter:
(0.112 inches
٦	Thready Qty Per Inch (tpi):
4	10
ſ	/in. Tensile Strength (psi):
	60000 pounds per square inch
ł	Externally Relieved Body Diameter Quantity:
ł	Product Name:
1	lavy special project
I	Naterial:
I	ron alloy 660
I	Naterial Specification:
/	Ams 5737 assn standard single material response
ę	Surface Treatment:
F	Passivate
ę	Surface Treatment Specification:
(Qq-p-35 federal specification single treatment response
٦	Thread Series Designator:
ι	Jnc
\$	Shelf Life:
	V/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0