NSN 5305-00-007-1581

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-1581 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.656 inches and 0.661 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.255 inches and 0.270 inches **Head Height:** Between 0.088 inches and 0.102 inches **First Diameter From Head:** Between 0.109 inches and 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.406 inches and 0.411 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-007-1581

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0