## NSN 5305-00-007-1710

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-1710 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 1.000 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.620 inches **Head Height:** 0.500 inches **First Diameter From Head:** Between 0.310 inches and 0.340 inches **Second Diameter From Head:** Between 0.175 inches and 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.340 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.750 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, e300, f-16 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-00-007-1710

Externally Relieved Body Screw - Page 2 of 2



Unit	Of	Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.