
Socket Head Cap Screw - Page 1 of 2



AeroBase

Group

View Online at https://aerobasegroup.com/nsn/5305-00-007-2962

Ja Thread Direction: Right-hand Thread Length: Between 0.797 inches and 0.891 inches Fastner Length: Between 0.859 inches and 0.891 inches Head Style: Flat chamfer Head Dimeter: Between 0.306 inches and 0.313 inches Head Height: Between 0.108 inches and 0.118 inches Locking Feature: Patch threads Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches Thread Diameter: 100000 pounds per square inch Surface Finish: 32 Min Tensile Strength (psi): 1100000 pounds per square inch Surface Treatment Pasivale Quep-35 federal specification: Quep-35 federal specification Quep-35 federal specification single treatme	Thread Class:
Turead Direction: Right-hand Turead Length: Between 0.797 inches and 0.891 inches Fastoner Length: Between 0.859 inches and 0.891 inches Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.313 inches Head Height: Between 0.103 inches and 0.118 inches Locking Feature: Patch threads Internal Drive Style: Offset cruciform (torque set) Thready Diameter: 0.190 inches 190 inches Thready Diameter: 0.190 inches Thready Diameter: 0.190 inches Thready Diameter: 0.190 inches Thready Styper Inch (tpi): 32 Min-Casile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Nay special project Material: Torad Strength (psi): 1010 folgo Surface Treatment: Passivate Surfa	
Right-hand Tread Length: Between 0.797 inches and 0.891 inches Fastener Length: Between 0.859 inches and 0.891 inches Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.313 inches Head Height: Between 0.103 inches and 0.313 inches Locking Feature: Patch threads Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches Thread Valve Funch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32. Navy special project Material: Ion alloy 660 Surface Treatment Specification: Qassivate Dirace Treatment Specification: Qassivate Surface Treatment Specification: Qassivate Surface Treatment Specification: Qassivate Burdie: Qator Assivate Surface Treatment Specification: Qassivate Surface Treatment Specification: Qassivate Burdie: Qator Assivate Surface Treatment Specification: Qator Assivate Burdie: Datasi Specification Data: Rozofication Pata: Rozofication Pata: Rozofication Pata: Rozofication Pata: Rozofication Pata: R	
Tread Length: Between 0.797 inches and 0.891 inches Fastener Length: Between 0.859 inches and 0.891 inches Head Style: Flat chamfer Head Diameter: Between 0.030 inches and 0.313 inches Head Height: Between 0.103 inches and 0.118 inches Locking Feature: Patch threads Interal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches 101 for cruciform (torque set) Thread Diameter: 0.190 inches 101 for cruciform (torque set) Thread Diameter: 0.190 inches 10200 pounds per square inch Surface Finish: 320 Product Name: Navy special project Material: Iron alloy 660 Surface Treatment Specification: Ioral Specification single treatment response Thread Specification single treatment response Thread Specification standard Specification Data: Autoris Autoris	
Particles and 0.891 inches Fastener Length: Between 0.859 inches and 0.891 inches Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.313 inches Head Height: Between 0.306 inches and 0.313 inches Head The Style: Outsin Feature: Patch threads Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Surface Treatment: Passivate Garcea Treatment Specification single treatment response Thread Series Designator:	-
Fastener Length: Between 0.859 inches and 0.891 inches Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.313 inches Head Height: Between 0.103 inches and 0.118 inches Locking Feature: Patch threads Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches Thread Style Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Internal Drive Style: Navy special project Material: Iron alloy 660 Surface Treatment Specification Aug-35 federal specification single treatment response Thread Series Designator: Unjr Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: Na	-
Between 0.859 inches and 0.891 inches Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.313 inches Head Height: Between 0.103 inches and 0.118 inches Locking Feature: Path threads Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Style: 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Ironaloy 660 Surface Treatment Specification: Oaqp-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: Bo205-nas1743 professional/industrial association standard Shelf Life: N/a	
Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.313 inches Head Height: Between 0.103 inches and 0.118 inches Locking Feature: Patch threads Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Part (torque set) Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Surface Treatment Specification: Quep-35 federal specification: Quep-35 federal specification single treatment response Thread Series Designator: Unif Su205-nas1743 professional/industrial association standard Su205-nas1743 professional/industrial association standard	-
Flat chamfer Head Diameter: Between 0.306 inches and 0.313 inches Head Height: Between 0.103 inches and 0.118 inches Locking Feature: Patch threads Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Surface Treatment: Pasivate Que-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: Nav	Head Style:
Between 0.306 inches and 0.313 inches Head Height: Between 0.103 inches and 0.118 inches Locking Feature: Patch threads Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches Thready Cty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Surface Treatment: Passivate Auge-35 federal specification Inge-15 besignator: Inge-35 federal specification single treatment response Thread Series Designator: Inge Su205-nas1743 professional/industrial association standard Shelf Life: Nva	-
Head Height:Between 0.103 inches and 0.118 inchesLocking Feature:Patch threadsInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.190 inchesThready Cty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsProduct Name:Navy special projectMaterial:Iron alloy 660Surface Treatment:PassivateSurface Treatment:Qap-35 federal specification single treatment responseThread Series Designator:UnifSpecification Data:8205-nas1743 professional/industrial association standardKatNavNavSurface Time National Specification standardSurface InsterSurface National Specification standardSurface National Specification Specification standardSurface National Specification SpecificatiO	Head Diameter:
Between 0.103 inches and 0.118 inches Locking Feature: Patch threads Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Surface Treatment Specification: Qap-35 federal specification single treatment response Thread Sries Designator: Unif Specification Data: 8205-nas1743 professional/industrial association standard Net	Between 0.306 inches and 0.313 inches
Locking Feature: Patch threads Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Surface Treatment Specification: Qap-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 8205-nas1743 professional/industrial association standard Net	Head Height:
Patch threadsInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.190 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsProduct Name:Navy special projectMaterial:Iron alloy 660Surface Treatment:Qap-35 federal specificationQue-35 federal specification single treatment responseThread Series Designator:UnifSpecification Data:Ro205-nas1743 professional/industrial association standardNva	Between 0.103 inches and 0.118 inches
Internal Drive Style:Offset cruciform (torque set)Thread Diameter:0.190 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsProduct Name:Navy special projectMaterial:Iron alloy 660Surface Treatment Specification:Qap-35 federal specification single treatment responseThread Series Designator:UnifSpecification Data:R0205-nas1743 professional/industrial association standardNaNa	Locking Feature:
Offset cruciform (torque set) Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Surface Treatment Specification: Qap-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1743 professional/industrial association standardNa'	Patch threads
Thread Diameter:0.190 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsProduct Name:Navy special projectMaterial:Iron alloy 660Surface Treatment:PassivateSurface Treatment SpecificationQu-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas1743 professional/industrial association standardNia	Internal Drive Style:
0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: N/a	Offset cruciform (torque set)
Thready Qty Per Inch (tpi):32Jan. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsProduct Name:Navy special projectMaterial:Iron alloy 660Surface Treatment:PassivateQrg-p-35 federal specification single treatment responseThread Series Designator:UnifSpecification Data:80205-nas1743 professional/industrial association standardN/a	Thread Diameter:
32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Inon alloy 660 Surface Treatment: Passivate Surface Treatment Specification Guq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life:	0.190 inches
Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsProduct Name:Navy special projectMaterial:Iron alloy 660Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas1743 professional/industrial association standardShelf Life:N/a	Thready Qty Per Inch (tpi):
 160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: N/a 	32
Surface Finish:32.0 microinches threadsProduct Name:Navy special projectMaterial:Iron alloy 660Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas1743 professional/industrial association standardShelf Life:N/a	Min. Tensile Strength (psi):
32.0 microinches threadsProduct Name:Navy special projectMaterial:Iron alloy 660Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas1743 professional/industrial association standardShelf Life:N/a	160000 pounds per square inch
Product Name:Navy special projectMaterial:Iron alloy 660Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas1743 professional/industrial association standardShelf Life:N/a	Surface Finish:
Navy special project Meterial: Iron alloy 660 Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: N/a	32.0 microinches threads
Material:Iron alloy 660Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas1743 professional/industrial association standardShelf Life:N/a	Product Name:
Iron alloy 660 Surface Treatment: Passivate Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: N/a	Navy special project
Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas1743 professional/industrial association standardShelf Life:N/a	Material:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: N/a	Iron alloy 660
Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: N/a	Surface Treatment:
Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas1743 professional/industrial association standardShelf Life:N/a	Passivate
Thread Series Designator: Unjf Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: N/a	Surface Treatment Specification:
Unjf Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: N/a	Qq-p-35 federal specification single treatment response
Specification Data: 80205-nas1743 professional/industrial association standard Shelf Life: N/a	Thread Series Designator:
80205-nas1743 professional/industrial association standard Shelf Life: N/a	Unjf
Shelf Life: N/a	Specification Data:
N/a	
Unit Of Measure:	
	Unit Of Measure:

NSN 5305-00-007-2962

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

