## NSN 5305-00-007-3066

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-3066 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** Between 1.813 inches and 1.875 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.088 inches and 0.102 inches **First Diameter From Head:** 0.164 inches **Second Diameter From Head:** Between 0.105 inches and 0.115 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.047 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.813 inches and 0.875 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Product Name:** Navy special project Material: Iron alloy 660 **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-007-3066

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0