NSN 5305-00-007-3261

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-3261 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.3594 inches and 0.4530 inches **Fastener Length:** Between 0.5938 inches and 0.6562 inches **Head Style:** Round extended washer **Head Diameter:** Between 0.365 inches and 0.385 inches **Head Height:** Between 0.089 inches and 0.099 inches **Extended Washer Diameter:** Between 0.427 inches and 0.447 inches **Extended Washer Thickness:** Between 0.025 inches and 0.030 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Material: Steel comp 4037 or steel comp 8630 **Material Specification:** Mil-s-8695 military specification 1st material response or mil-s-6050 military specification 2nd material response **Surface Treatment:** Cadmium and chromate or zinc **Surface Treatment Specification:** Qq-p-416 ty2 federal specification 1st treatment response or astm b633 assn standard 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-007-3261

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8695 spec.