## NSN 5305-00-007-6212

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-6212 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.219 inches **Fastener Length:** Between 0.719 inches and 0.724 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.221 inches and 0.226 inches **Head Height:** Between 0.074 inches and 0.086 inches **First Diameter From Head:** Between 0.081 inches and 0.086 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.500 inches and 0.505 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-007-6212

Externally Relieved Body Screw - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A003b0