NSN 5305-00-007-6214

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-6214 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.719 inches and 0.724 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.265 inches and 0.270 inches **Head Height:** Between 0.088 inches and 0.102 inches **First Diameter From Head:** Between 0.109 inches and 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.469 inches and 0.474 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-00-007-6214

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0