Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-6218

т	hread Class:
3	
-	a hread Direction:
	ight-hand
	hread Length:
	.250 inches
-	astener Length:
	etween 0.781 inches and 0.786 inches
	lead Style:
	lat chamfer
	lead Diameter:
	etween 0.255 inches and 0.270 inches
	lead Height:
	etween 0.088 inches and 0.102 inches
	irst Diameter From Head:
	etween 0.109 inches and 0.114 inches
D	istance From Largest Bearing Surface Of Head To End Of First Diameter:
	etween 0.531 inches and 0.536 inches
Ir	nternal Drive Style:
С	offset cruciform (torque set)
т	hread Diameter:
0	.164 inches
т	hready Qty Per Inch (tpi):
3	2
N	lin. Tensile Strength (psi):
1	60000 pounds per square inch
E	xternally Relieved Body Diameter Quantity:
1	
Ρ	roduct Name:
Ν	avy special project
N	laterial:
Ir	on alloy 660
N	laterial Specification:
	ms 5737 assn standard single material response
S	urface Treatment:
Ρ	assivate
	urface Treatment Specification:
C	q-p-35 federal specification single treatment response
Т	hread Series Designator:
	njc
S	helf Life:
Ν	/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0