Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-007-6223

Thread Class:
3a Thread Direction:
Right-hand
Thread Length:
Between 0.226 inches and 0.267 inches
Fastener Length:
Between 0.531 inches and 0.562 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.265 inches and 0.270 inches
Head Height:
Between 0.088 inches and 0.102 inches
First Diameter From Head:
Between 0.120 inches and 0.125 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.295 inches and 0.305 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Externally Relieved Body Diameter Quantity:
1
Special Features:
Elocking feature loc-well type on threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0