

View Online at <https://aerobasegroup.com/nsn/5305-00-008-3701>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.251 inches and 0.301 inches

Fastener Length:

Between 0.823 inches and 0.853 inches

Head Style:

Fillister

Head Diameter:

Between 0.265 inches and 0.270 inches

Head Height:

Between 0.088 inches and 0.102 inches

Grip Diameter:

Between 0.1625 inches and 0.1635 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.164 inches

Grip Length:

Between 0.552 inches and 0.572 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches bearing surface of head

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1122 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.