Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-008-5840

Inread Direction:         Paread Direction:         Right-hand         Thread Length:         Between 0.169 inches and 0.207 inches         Fastener Length:         0.625 inches         Head Style:         Fillister         Head Diameter:         Between 0.208 inches and 0.226 inches         Head Height:         Between 0.086 inches and 0.226 inches         Head Height:         Between 0.086 inches and 0.100 inches         First Diameter From Head:         Between 0.397 inches and 0.417 inches         Internal Drive Style:         Stot         Thread Diameter:         0.138 inches         Thread Diameter:         0.138 inches         Thread Diameter:         0.138 inches         Thread Diameter:         0.138 inches         Thread Jameter:         0.138 inches         Thread Style Boot foderal specification single material response         Surface Treatment:         Nickel         Thread Series Designator:         Unc         Shell Life:         Na         Ditt Of Measure:         -         Demiliarization:	
Thread Direction:         Right-hand         Thread Length:         Between 0.169 inches and 0.207 inches         Fastener Length:         0.625 inches         Head Style:         Fillister         Head Diameter:         Between 0.028 inches and 0.226 inches         Head Height:         Between 0.028 inches and 0.226 inches         First Diameter From Head:         Between 0.090 inches and 0.100 inches         First Diameter From Head:         Between 0.397 inches and 0.417 inches         Heread Diameter:         0.138 inches         Thread Diameter:         0.138 inches         Thread Diameter:         0.138 inches         Thread Diameter:         0.138 inches         Thread Style Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material         Copper alloy 360 federal specification single material response         Marcial Specification:         Queb -626 alloy 360 federal specification single material response         Marcial Specification:         Nickel         Thread Style Subsignator:         Na'         Mare	Thread Class:
Right-hand         Thread Length:         Between 0.169 inches and 0.207 inches         Fastener Length:         0.625 inches         Head Style:         Fillister         Head Diameter:         Between 0.208 inches and 0.226 inches         Head Height:         Between 0.086 inches and 0.096 inches         Fillister         Between 0.090 inches and 0.096 inches         Distance From Head:         Between 0.397 inches and 0.100 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         Between 0.397 inches and 0.417 inches         Internal Drive Style:         Slot         Thread Diameter:         0.138 inches         Thready Gty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Copper alloy 360         Material Specification:         Nickel         Thread Series Designator:         Unc         Sheff Life:         Nickel         Thread Series Designator:         Incher         Sheff Life:         Nickel         Thread Series Designator: <th></th>	
Tread Length:         Between 0.169 inches and 0.207 inches         Fastener Length:         0.625 inches         Head Style:         Fillister         Head Diameter:         Between 0.208 inches and 0.226 inches         Head Height:         Between 0.086 inches and 0.096 inches         Fillister         Between 0.086 inches and 0.096 inches         Fortbaneter From Head:         Between 0.090 inches and 0.100 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         Between 0.397 inches and 0.417 inches         Internal Drive Style:         Stot         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Matrial:         Capper alloy 360         Matrial Specification:         Quad-b628 alloy 360 federal specification single material response         Surface Treatment:         Nickel         Thread Series Designator:         Nickel         Cher         Surface Treatment:         Nickel         Finet Life:         Nickel	
Between 0.169 inches and 0.207 inches         Fastener Length:         0.625 inches         Head Style:         Fillister         Head Diameter:         Between 0.208 inches and 0.226 inches         Head Height:         Between 0.086 inches and 0.096 inches         First Diameter From Head:         Between 0.090 inches and 0.100 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         Between 0.397 inches and 0.417 inches         Internal Drive Style:         Stot         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Extremally Relieved Body Diameter Quantity:         1         Material:         Copper alloy 360         Material Specification:         Quade Style:         Nickel         Thread Style:         Nickel         Thread Style:         Nickel         Quade Style:         Distance:         Nickel         Thread Diameter:         Nickel         Head Diameter:         Nickel         Dire:         Nickel	-
Fastener Length:         0.625 inches         Head Style:         Fillister         Head Diameter:         Between 0.208 inches and 0.226 inches         Head Height:         Between 0.086 inches and 0.096 inches         First Diameter From Head:         Between 0.090 inches and 0.100 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         Between 0.397 inches and 0.417 inches         Internal Drive Style:         Stot         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material Specification:         Cape-626 alloy 360 federal specification single material response         Surface Treatment:         Nickel         Thread Series Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:         r-         Demilitarization:         No         Fig:	-
0.625 inchesHead Style:FillisterHead Diameter:Between 0.208 inches and 0.226 inchesHead Height:Between 0.086 inches and 0.096 inchesFirst Diameter From Head:Between 0.090 inches and 0.100 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 0.397 inches and 0.417 inchesInternal Drive Style:SlotThread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Externally Relieved Body Diameter Quantity:1Material:Copper alloy 360 federal specification single material responseSurface Treatment:NickelThread Steries Designator:UncSurface Ineation:NickelChreat Steries Designator:NickelNickelNickelNickelNickelSuffice:NickelFire:NickelFire:NickelFire:NickelFire:NickelFire:NickelFire:NickelFire:NickelFire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:Fire:<	
Head Style:   Fillister   Head Diameter:   Between 0.208 inches and 0.226 inches   Head Height:   Between 0.086 inches and 0.096 inches   First Diameter From Head:   Between 0.090 inches and 0.100 inches   Distance From Largest Bearing Surface Of Head To End Of First Diameter:   Between 0.397 inches and 0.417 inches   Internal Drive Style:   Slot   Thread Diameter:   0.138 inches   Thready Qty Per Inch (tpl):   32   Externally Relieved Body Diameter Quantity:   1   Material:   Copper alloy 360   Material:   Qa-b-626 alloy 360 federal specification single material response   Surface Treatment:   Nickel   Thread Series Designator:   Unc   Sheft Life:   N/a   Nickel   Thread Series Designator:   Na   Nickel   Firster:   Na   Firster:   Na   Firster:   Na   Firster:   Na   Ster:   Na   Na   Na   Hader:   Na   Ster:   Na   Ster:   Na   Ster:   Na   Ster:   Ster:   Ster:   Ster:   Ster:   Ster:   Ster:   Ster:   Ster:   Ster: <td></td>	
FilisterHead Diameter:Between 0.208 inches and 0.226 inchesHead Height:Between 0.086 inches and 0.096 inchesFirst Diameter From Head:Between 0.090 inches and 0.100 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 0.397 inches and 0.417 inchesInternal Drive Style:SlotThread Diameter:0.138 inchesThread Diameter:32Externally Relieved Body Diameter Quantity:1Material:Copper alloy 360Material:NickelThread Steines Designator:NickelFired Steines Designator:NickelChrief Life:NickelInterd Steines Designator:NickelNickelFired Steines Designator:NickelNickelSteines Designator:NickelFired Steines Designator:NickelFired Steines Designator:NickelFired Steines Designator:NickelFired Steines Designator:NickelSteinet Differition:NickelSteinet Differition:NickelSteinet Differition:NickelSteinet Differition:NickelSteinet Differition:Steinet Differition:Steinet Differition:Steinet Differition:Steinet Differition:Steinet Differition:Steinet Differition:Stei	
Head Diameter:         Between 0.208 inches and 0.226 inches         Head Height:         Between 0.086 inches and 0.096 inches         First Diameter From Head:         Between 0.090 inches and 0.100 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         Between 0.397 inches and 0.417 inches         Internal Drive Style:         Slot         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Coper alloy 360         Material:         Qu-b-626 alloy 360 federal specification single material response         Surface Treatment:         Nickel         Thread Series Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:         r         Pomilitarization:         No         Fig:	Head Style:
Between 0.208 inches and 0.226 inches Head Height: Between 0.086 inches and 0.096 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.397 inches and 0.417 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification Qu-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Nick Fig:	
Head Height:         Between 0.086 inches and 0.096 inches         First Diameter From Head:         Between 0.090 inches and 0.100 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         Between 0.397 inches and 0.417 inches         Internal Drive Style:         Slot         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Copper alloy 360         Material Specification:         Qq-b-626 alloy 360 federal specification single material response         Surface Treatment:         Nickel         Thread Series Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         No         Fig:	Head Diameter:
Between 0.086 inches and 0.096 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.397 inches and 0.417 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - No Fig:	Between 0.208 inches and 0.226 inches
First Diameter From Head:   Between 0.090 inches and 0.100 inches   Distance From Largest Bearing Surface Of Head To End Of First Diameter:   Between 0.397 inches and 0.417 inches   Internal Drive Style:   Slot   Thread Diameter:   0.138 inches   Thready Qty Per Inch (tpi):   32   Externally Relieved Body Diameter Quantity:   1   Material:   Copper alloy 360   Material Specification:   Qu-b-626 alloy 360 federal specification single material response   Surface Treatment:   Nickel   Thread Series Designator:   Iunc   Material:   Ord Measure:     Na   Diric f Measure:       Pinemal Series Designator:   Iunc   Shelf Life:   Na   Internal Series Designator:     Iunc   Fig:	Head Height:
Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.397 inches and 0.417 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Between 0.086 inches and 0.096 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.397 inches and 0.417 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No	First Diameter From Head:
Between 0.397 inches and 0.417 inches Internal Drive Style: Slot Thread Diameter: O.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.090 inches and 0.100 inches
Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 f Material: Copper alloy 360 Material Specification: Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	Between 0.397 inches and 0.417 inches
Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Internal Drive Style:
0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Slot
Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Copper alloy 360 federal specification single material response Material Specification: Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Thread Diameter:
32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Cop-626 alloy 360 federal specification single material response Surface Treatment: Nickel Mickel Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure:  Fig:	0.138 inches
Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Thready Qty Per Inch (tpi):
1Material:Copper alloy 360Material Specification:Qq-b-626 alloy 360 federal specification single material responseSurface Treatment:NickelThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	32
Material:Copper alloy 360Material Specification:Qq-b-626 alloy 360 federal specification single material responseSurface Treatment:NickelThread Series Designator:UncShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	Externally Relieved Body Diameter Quantity:
Copper alloy 360 Material Specification: Qq-b-626 alloy 360 federal specification single material response Surface Treatment: Nickel Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Fig:	1
Material Specification:   Qq-b-626 alloy 360 federal specification single material response   Surface Treatment:   Nickel   Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Material:
Qq-b-626 alloy 360 federal specification single material response   Surface Treatment:   Nickel   Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Copper alloy 360
Surface Treatment: Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Material Specification:
Nickel Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Qq-b-626 alloy 360 federal specification single material response
Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Surface Treatment:
Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Nickel
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Thread Series Designator:
N/a Unit Of Measure:  Demilitarization: No Fiig:	Unc
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
-	Fiig:
	-