NSN 5305-00-008-5888

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-008-5888 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.600 inches and 0.693 inches Fastener Length: Between 0.719 inches and 0.750 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.231 inches and 0.279 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1102 professional/industrial association standard Shelf Life: N I / -

IN/a
Unit Of Measure
Demilitarization:
No

NSN 5305-00-008-5888

Machine Screw - Page 2 of 2



Fiig:

A500d0