## NSN 5305-00-008-5898



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-008-5898 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.169 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.178 inches and 0.183 inches **Head Height:** Between 0.059 inches and 0.069 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 32.0 microinches threads Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Surface Treatment:** 

Cadmium and chromate

### **Surface Treatment Specification:**

Qq-p-416, type2, class3 federal specification all treatment responses

#### **Thread Series Designator:**

Unjc

#### **Specification Data:**

80205-nas1191 professional/industrial association standard

### Shelf Life:

N/a

#### **Unit Of Measure:**

# NSN 5305-00-008-5898

Socket Head Cap Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.