## NSN 5305-00-008-5912

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-008-5912 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.199 inches and 0.259 inches **Fastener Length:** Between 0.454 inches and 0.484 inches **Head Style:** Flat countersunk **Head Diameter:** 0.223 inches **Shoulder Diameter:** 0.141 inches first shoulder and 0.143 inches first shoulder **Shoulder Length:** 0.185 inches first shoulder and 0.215 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 33.0 rockwell c and 37.0 rockwell c **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp 8740 or steel comp 4037 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5305-00-008-5912** Shoulder Screw - Page 2 of 2



Fiig:

A003b0