NSN 5305-00-008-9055

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-008-9055

view Online a	thttps://aerobasegroup.com/nsn/5305-00-008-9055
Thread Class	s:
3a	
Thread Direc	tion:
Right-hand	
Thread Leng	th:
Between 0.41	5 inches and 0.456 inches
Fastener Len	gth:
Between 1.62	3 inches and 1.663 inches
Head Style:	
Pan	
Head Diamet	er:
Between 0.67	1 inches and 0.709 inches
Head Height:	
Between 0.19	1 inches and 0.215 inches
Shoulder Dia	meter:
0.371 inches	and 0.374 inches first shoulder
Shoulder Ler	ngth:
1.135 inches	and 1.155 inches first shoulder
Internal Drive	e Style:
Cross recess	type 1
Thread Diam	eter:
0.312 inches	
Thready Qty	Per Inch (tpi):
24	
Min. Tensile	Strength (psi):
125000 pound	ds per square inch
Hardness Ra	ting:
26.0 rockwell	c and 32.0 rockwell c
Shoulder Sha	аре:
Round first sh	oulder
Product Nam	e:
Navy special ¡	project
Material:	
Steel comp 40	037 or steel comp 8630
Surface Trea	tment:
Cadmium and	d chromate
Surface Trea	tment Specification:
Qq-p-416, typ	e 2, class 3 federal specification single treatment response
Thread Serie	s Designator:
Unf	
Specification	Data:
80205-nas120	98 professional/industrial association standard

80205-nas1298 professional/industrial association standard

NSN 5305-00-008-9055

Shoulder Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0