NSN 5305-00-008-9055

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-008-9055



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.415 inches and 0.456 inches Fastener Length: Between 1.623 inches and 1.663 inches **Head Style:** Pan **Head Diameter:** Between 0.671 inches and 0.709 inches **Head Height:** Between 0.191 inches and 0.215 inches **Shoulder Diameter:** 0.371 inches and 0.374 inches first shoulder Shoulder Length: 1.135 inches and 1.155 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Shoulder Shape: Round first shoulder **Product Name:** Navy special project Material: Steel comp 4037 or steel comp 8630 Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Data:**

80205-nas1298 professional/industrial association standard

NSN 5305-00-008-9055

Shoulder Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

