NSN 5305-00-008-9283

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-008-9283 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.270 inches and 0.322 inches **Fastener Length:** Between 0.780 inches and 0.812 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.088 inches and 0.102 inches **First Diameter From Head:** 0.164 inches **Second Diameter From Head:** Between 0.105 inches and 0.115 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.037 inches and 0.057 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.490 inches and 0.510 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Product Name:** Navy special project Material: Iron alloy 660 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-008-9283

Externally Relieved Body Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.