

View Online at <https://aerobasegroup.com/nsn/5305-00-009-5659>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.125 inches

**Fastener Length:**

1.250 inches

**Head Style:**

Headless (setscrew)

**Locking Feature:**

Patch threads or strip threads

**Point Length:**

Between 0.115 inches and 0.125 inches

**Point Diameter:**

0.876 inches

**Point Style:**

Dog

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.938 inches

**Width Across Flats:**

0.328 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

34.0 rockwell c and 42.0 rockwell c

**Product Name:**

Navy special project

**Special Features:**

Nonstandard point concave to 0.750 in. Radius

**Material:**

Steel comp 4130

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0