Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-009-7701

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.200 inches and 0.210 inches
Fastener Length:
Between 0.415 inches and 0.425 inches
Head Style:
Pan
Head Diameter:
Between 0.205 inches and 0.219 inches
Head Height:
Between 0.070 inches and 0.080 inches
First Diameter From Head:
Between 0.075 inches and 0.085 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.215 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
140000 pounds per square inch
Externally Relieved Body Diameter Quantity:
1
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
-

Externally Relieved Body Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

