NSN 5305-00-009-7702

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-009-7702 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.145 inches and 0.155 inches **Fastener Length:** Between 0.540 inches and 0.550 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.075 inches and 0.085 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.340 inches and 0.360 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-009-7702

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0