NSN 5305-00-009-9264

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-009-9264 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.219 inches **Fastener Length:** Between 0.781 inches and 0.786 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.221 inches and 0.226 inches **Head Height:** Between 0.074 inches and 0.086 inches **First Diameter From Head:** Between 0.081 inches and 0.086 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.562 inches and 0.567 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment:** Chromium **Surface Treatment Specification:** Mil-c-11436 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-009-9264

Externally Relieved Body Screw - Page 2 of 2



Unit	Of	Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-11436 spec.