NSN 5305-00-010-2870

Setscrew - Page 1 of 2



Vi

| /iew Online at https://aerobasegroup.com/nsn/5305-00-010-2870 | |
|--|--|
| Thread Class: | |
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Fhread Length: | |
| Between 0.469 inches and 0.500 inches | |
| Fastener Length: | |
| Between 0.469 inches and 0.531 inches | |
| Head Style: | |
| Square | |
| Head Height: | |
| Between 0.178 inches and 0.196 inches | |
| Nidth Between Flats: | |
| Between 0.241 inches and 0.250 inches | |
| Point Style: | |
| Cup | |
| nternal Drive Style: | |
| N/o internal drive | |
| Thread Diameter: | |
| 0.250 inches | |
| Features Provided: | |
| Casehardened | |
| Γhready Qty Per Inch (tpi): | |
| 20 | |
| Hardness Rating: | |
| 30.0 rockwell c and 37.0 rockwell c | |
| Material: | |
| Steel comp 1010 or steel comp 1020 | |
| Material Specification: | |
| 66 federal standard all material responses or sae j403 uns g10100 through g10200 assn standard all material responses | |
| Supplementary Features: | |
| Natural fin. Unplated/uncoated | |
| Thread Series Designator: | |
| Jnc State of the s | |
| Specification Data: | |
| 31348-ff-s-210 government specification and 80204-ansi b18.6.2 professional/industrial association standard and 24617-102870 | |
| nanufacturers standard and 11757-500568 manufacturers standard | |
| Specification Or Standard: | |
| type and 4 style and 1/4.In size and 1/2in. Length and 4 table | |
| Shelf Life: | |
| N/a | |
| Jnit Of Measure: | |

NSN 5305-00-010-2870

Setscrew - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0