NSN 5305-00-012-6135

Setscrew - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-012-6135

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.375 inches
Fastener Length:
0.375 inches
Head Style:
Headless (setscrew)
Point Style:
Cup
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Features Provided:
Casehardened
Thready Qty Per Inch (tpi):
32
Hardness Rating:
Hardness Rating: 30.0 rockwell c and 37.0 rockwell c
-
30.0 rockwell c and 37.0 rockwell c
30.0 rockwell c and 37.0 rockwell c Material:
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification:
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment:
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium or zinc
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium or zinc Thread Series Designator:
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium or zinc Thread Series Designator: Unf
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium or zinc Thread Series Designator: Unf Specification Or Standard:
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium or zinc Thread Series Designator: Unf Specification Or Standard: 2 type and 4 style
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium or zinc Thread Series Designator: Unf Specification Or Standard: 2 type and 4 style Shelf Life:
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium or zinc Thread Series Designator: Unf Specification Or Standard: 2 type and 4 style Shelf Life: N/a
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium or zinc Thread Series Designator: Unf Specification Or Standard: 2 type and 4 style Shelf Life: N/a
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium or zinc Thread Series Designator: Unf Specification Or Standard: 2 type and 4 style Shelf Life: N/a Unit Of Measure:
30.0 rockwell c and 37.0 rockwell c Material: Steel comp 1010 or steel comp 1020 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium or zinc Thread Series Designator: Unf Specification Or Standard: 2 type and 4 style Shelf Life: N/a Unit Of Measure: Demilitarization: