NSN 5305-00-013-3414

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-013-3414 **Thread Class:** 2a **Thread Direction:** Right-hand **Thread Length:** 0.167 inches **Fastener Length:** 0.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.249 inches and 0.279 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material Specification:** Qq-s-633 except bessemer comp federal specification 1st material response or qq-w-409 federal specification 2nd material response or qq-w-409 federal specification 3rd material response or qq-w-409 federal specification 4th material response or qq-w-409 federal specification 5th material response or qq-w-409, grade 3 federal specification 6th material response or qq-w-409 federal specification 7th material response or qq-w-409 federal specification 8th material response or qq-w-409 federal specification 9th material response or qq-w-409 federal specification 10th material response or qq-w-409 federal specification 11th material response or qq-w-409 federal specification 12th material response or qq-w-409 federal specification 13th material response or qq-w-409 federal specification 14th material **Screw Surface Treatment:** Cadmium and dichromate or zinc and dichromate **Thread Series Designator: Specification Or Standard:** I type and 2s style Shelf Life: N/a **Unit Of Measure:**

No Fiig:

A500d0

Demilitarization: