

View Online at <https://aerobasegroup.com/nsn/5305-00-013-3414>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.167 inches

Fastener Length:

0.250 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.249 inches and 0.279 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material Specification:

Qq-s-633 except bessemer comp federal specification 1st material response or qq-w-409 federal specification 2nd material response or qq-w-409 federal specification 3rd material response or qq-w-409 federal specification 4th material response or qq-w-409 federal specification 5th material response or qq-w-409, grade 3 federal specification 6th material response or qq-w-409 federal specification 7th material response or qq-w-409 federal specification 8th material response or qq-w-409 federal specification 9th material response or qq-w-409 federal specification 10th material response or qq-w-409 federal specification 11th material response or qq-w-409 federal specification 12th material response or qq-w-409 federal specification 13th material response or qq-w-409 federal specification 14th material response

Screw Surface Treatment:

Cadmium and dichromate or zinc and dichromate

Thread Series Designator:

Unc

Specification Or Standard:

1 type and 2s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0