

View Online at <https://aerobasegroup.com/nsn/5305-00-013-3427>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.406 inches and 0.437 inches

Fastener Length:

Between 0.406 inches and 0.437 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.257 inches and 0.279 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

60000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material:

Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050

Screw Material Specification:

Qq-s-634 federal specification all material responses

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416, type 2, cl c federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

I type and 2s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0