

View Online at <https://aerobasegroup.com/nsn/5305-00-013-3444>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.761 inches and 0.792 inches

Fastener Length:

Between 0.844 inches and 0.875 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.249 inches and 0.279 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material:

Steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1527 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1038 or steel comp 1040 or steel comp 1541

Screw Material Specification:

Qq-s-633 federal specification all material responses or qq-w-409 federal specification all material responses

Screw Surface Treatment:

Cadmium and chromate or zinc and chromate

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0