

View Online at <https://aerobasegroup.com/nsn/5305-00-013-3573>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.844 inches and 0.875 inches

**Fastener Length:**

Between 0.844 inches and 0.875 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.359 inches and 0.385 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020

**Screw Material Specification:**

Qq-s-634 federal specification all material responses

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416, type 2, cl c federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

I type and 2s style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0