

View Online at <https://aerobasegroup.com/nsn/5305-00-014-7865>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.847 inches

Fastener Length:

1.000 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.477 inches and 0.507 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

55000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material:

Steel or steel or steel or steel comp 1025 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1038 or steel comp 1040 or steel comp 1045

Screw Material Specification:

Qq-s-633-canc federal specification 1st material response or qq-w-409, grade 2 federal specification 2nd material response or qq-w-409, grade 3 federal specification 3rd material response or qq-w-409, grade 4 federal specification 4th material response or qq-w-409, grade 4 federal specification 5th material response or qq-w-409, grade 4 federal specification all material responses or qq-w-409, grade 4 federal specification 6th material response or qq-w-409, grade 4 federal specification 7th material response or qq-w-409, grade 4 federal specification 8th material response or qq-w-409, grade 4 federal specification 9th material response or qq-w-409, grade 4 federal specification 10th material response

Thread Series Designator:

Unc

Specification Or Standard:

lil type and 2c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0