NSN 5305-00-015-1049

Wood Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-015-1049

Fastener Length: 2.500 inches Head Style: Round Head Diameter: Between 0.429 inches and 0.457 inches Head Height: Between 0.155 inches and 0.170 inches Internal Drive Style: Cross recess type 1 Nonmachine Thread Style: Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a Unit Of Measure:	
Head Style: Round Head Diameter: Between 0.429 inches and 0.457 inches Head Height: Between 0.155 inches and 0.170 inches Internal Drive Style: Cross recess type 1 Nonmachine Thread Style: Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a	
Round Head Diameter: Between 0.429 inches and 0.457 inches Head Height: Between 0.155 inches and 0.170 inches Internal Drive Style: Cross recess type 1 Nonmachine Thread Style: Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a	
Head Diameter: Between 0.429 inches and 0.457 inches Head Height: Between 0.155 inches and 0.170 inches Internal Drive Style: Cross recess type 1 Nonmachine Thread Style: Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a	
Between 0.429 inches and 0.457 inches Head Height: Between 0.155 inches and 0.170 inches Internal Drive Style: Cross recess type 1 Nonmachine Thread Style: Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a	
Head Height: Between 0.155 inches and 0.170 inches Internal Drive Style: Cross recess type 1 Nonmachine Thread Style: Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a	
Between 0.155 inches and 0.170 inches Internal Drive Style: Cross recess type 1 Nonmachine Thread Style: Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a	
Internal Drive Style: Cross recess type 1 Nonmachine Thread Style: Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a	
Cross recess type 1 Nonmachine Thread Style: Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a	
Nonmachine Thread Style: Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a	
Gimlet point (type a, ab or ba) Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response Shelf Life: N/a	
Nonmachine Thread Diameter: 0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response or qq-w-321 federal specification single material response Shelf Life: N/a	
0.242 inches Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response or qq-w-321 federal specification single material response Shelf Life: N/a	
Material: Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response or qq-w-321 federal specification single material response Shelf Life: N/a	
Copper alloy Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response or qq-w-321 federal specification single material response Shelf Life: N/a	
Material Specification: Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response or qq-w-321 federal specification single material response Shelf Life: N/a	
Qq-b-613, comp 6 or 7 federal specification single material response or qq-b-626, comp 6 or 7 federal specification single material response or qq-w-321 federal specification single material response Shelf Life: N/a	
or qq-w-321 federal specification single material response Shelf Life: N/a	
Shelf Life: N/a	ponse
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A003b0	