

View Online at <https://aerobasegroup.com/nsn/5305-00-016-7125>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.481 inches and 0.562 inches

Fastener Length:

Between 0.531 inches and 0.562 inches

Head Style:

Watertight

Head Diameter:

Between 0.205 inches and 0.238 inches

Head Height:

Between 0.070 inches and 0.080 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s; helicopter, search and rescue, hh-60h; deck machinery; helicopter, uscg search and rescue, hh-60j; helicopter, advance attack, ah-1w; helicopter, carrier based asw, sh-60f; airborne mine counter measure systems; towed array handling equipment; helicopter, mh-53e; surface torpedo tubes & ordalts; los angeles class ssn (688)

Thread Diameter:

0.112 inches

Features Provided:

O ring

Thready Qty Per Inch (tpi):

40

Screw Material:

Steel comp 304 or steel comp 305

Screw Material Specification:

66 federal standard all material responses

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0