## NSN 5305-00-016-8193



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-016-8193 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.376 inches **Fastener Length:** Between 2.641 inches and 2.688 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** 

Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

## NSN 5305-00-016-8193

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.