Hexagon Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-017-9797

Thread Class: 2a Thread Direction: Right-hand Thread Length: 0.750 inches Fastener Length: 1.000 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.437 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No	These di Olassa
Thread Direction:Right-handThread Length:0.750 inchesFastener Length:1.000 inchesHead Style:HexagonHead Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.437 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelThread Series Designator:UncSpecification Or Standard:2 type and 10p style and 5 gradeShelf Life:N/aUnit Of Measure:NoFiig:Kinge:Kinge:	
Right-handThread Length:0.750 inchesFastener Length:1.000 inchesHead Style:HexagonHead Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.437 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelThread Series Designator:UncSpecification Or Standard:2 type and 10p style and 5 gradeShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	
Thread Length:0.750 inchesFastener Length:1.000 inchesHead Style:Head Style:HexagonHead Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.437 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelThread Series Designator:UncSpecification Or Standard:2 type and 10p style and 5 gradeShelf Life:N/aUnit Of Measure:NoFiig:	
0.750 inches Fastener Length: 1.000 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.437 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No	•
Fastener Length:1.000 inchesHead Style:HexagonHead Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.437 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelThread Series Designator:UncSpecification Or Standard:2 type and 10p style and 5 gradeShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	-
1.000 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.437 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Head Style:HexagonHead Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.437 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelThread Series Designator:UncSpecification Or Standard:2 type and 10p style and 5 gradeShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	•
HexagonHead Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.437 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelThread Series Designator:UncSpecification Or Standard:2 type and 10p style and 5 gradeShelf Life:N/aUnit Of Measure:NoFiig:	1.000 inches
Head Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.437 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelThread Series Designator:UncSpecification Or Standard:2 type and 10p style and 5 gradeShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Head Style:
Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.437 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Hexagon
Width Between Flats: Between 0.428 inches and 0.437 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Head Height:
Between 0.428 inches and 0.437 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.150 inches and 0.163 inches
Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Width Between Flats:
0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.428 inches and 0.437 inches
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Diameter:
20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thready Qty Per Inch (tpi):
120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	20
Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Min. Tensile Strength (psi):
23.0 rockwell c and 32.0 rockwell c Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	120000 pounds per square inch
Material: Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Hardness Rating:
Steel Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	23.0 rockwell c and 32.0 rockwell c
Thread Series Designator: Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Unc Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel
Specification Or Standard: 2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Unc
2 type and 10p style and 5 grade Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Or Standard:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-
Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	N/a
 Demilitarization: No Fiig:	
No Fiig:	
No Fiig:	Demilitarization:
Fiig:	
-	
	A003b0
700300	700300