Hexagon Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-018-2718



Thread Class:2a2hread Direction:Right-handThread Length:1.000 inchesFastener Length:1.000 inchesHead Height:Between 0.226 inches and 0.243 inchesWidth Between Flats:Between 0.551 inches and 0.563 inchesThread Diameter:0.375 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelMaterial Specification:66 federal standard single material responseSurface Treatment:Phosphate and chromateThread Series Designator:UnfSpecification Or Standard:
Thread Direction:Right-handThread Length:1.000 inchesFastener Length:1.000 inchesHead Height:Between 0.226 inches and 0.243 inchesWidth Between Flats:Between 0.551 inches and 0.563 inchesThread Diameter:0.375 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelMaterial Specification:66 federal standard single material responseSurface Treatment:Phosphate and chromateThread Series Designator:UnfSpecification Or Standard:
Right-handThread Length:1.000 inchesFastener Length:1.000 inchesHead Height:Between 0.226 inches and 0.243 inchesWidth Between Flats:Between 0.551 inches and 0.563 inchesThread Diameter:0.375 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelMaterial Specification:66 federal standard single material responseSurface Treatment:Phosphate and chromateThread Series Designator:UnfSpecification Or Standard:
Thread Length:1.000 inchesFastener Length:1.000 inchesHead Height:Between 0.226 inches and 0.243 inchesWidth Between Flats:Between 0.551 inches and 0.563 inchesThread Diameter:0.375 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelMaterial Specification:66 federal standard single material responseSurface Treatment:Phosphate and chromateThread Series Designator:UnfSpecification Or Standard:
<ul> <li>1.000 inches</li> <li>Fastener Length:</li> <li>1.000 inches</li> <li>Head Height:</li> <li>Between 0.226 inches and 0.243 inches</li> <li>Width Between Flats:</li> <li>Between 0.551 inches and 0.563 inches</li> <li>Thread Diameter:</li> <li>0.375 inches</li> <li>Thready Qty Per Inch (tpi):</li> <li>24</li> <li>Min. Tensile Strength (psi):</li> <li>120000 pounds per square inch</li> <li>Hardness Rating:</li> <li>23.0 rockwell c and 32.0 rockwell c</li> <li>Material:</li> <li>Steel</li> <li>Material Specification:</li> <li>66 federal standard single material response</li> <li>Surface Treatment:</li> <li>Phosphate and chromate</li> <li>Thread Series Designator:</li> <li>Unf</li> <li>Specification Or Standard:</li> </ul>
Fastener Length:1.000 inchesHead Height:Between 0.226 inches and 0.243 inchesWidth Between Flats:Between 0.551 inches and 0.563 inchesThread Diameter:0.375 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelMaterial Specification:66 federal standard single material responseSurface Treatment:Phosphate and chromateThread Series Designator:UnfSpecification Or Standard:
<ul> <li>1.000 inches</li> <li>Head Height:</li> <li>Between 0.226 inches and 0.243 inches</li> <li>Width Between Flats:</li> <li>Between 0.551 inches and 0.563 inches</li> <li>Thread Diameter:</li> <li>0.375 inches</li> <li>Thready Qty Per Inch (tpi):</li> <li>24</li> <li>Min. Tensile Strength (psi):</li> <li>120000 pounds per square inch</li> <li>Hardness Rating:</li> <li>23.0 rockwell c and 32.0 rockwell c</li> <li>Material:</li> <li>Steel</li> <li>Material Specification:</li> <li>66 federal standard single material response</li> <li>Surface Treatment:</li> <li>Phosphate and chromate</li> <li>Thread Series Designator:</li> <li>Unf</li> <li>Specification Or Standard:</li> </ul>
Head Height:Between 0.226 inches and 0.243 inchesWidth Between Flats:Between 0.551 inches and 0.563 inchesThread Diameter:0.375 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):120000 pounds per square inchHardness Rating:23.0 rockwell c and 32.0 rockwell cMaterial:SteelMaterial Specification:66 federal standard single material responseSurface Treatment:Phosphate and chromateThread Series Designator:UnfSpecification Or Standard:
Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.563 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Width Between Flats: Between 0.551 inches and 0.563 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Between 0.551 inches and 0.563 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
24 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
23.0 rockwell c and 32.0 rockwell c Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Steel Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Material Specification: 66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
66 federal standard single material response Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Surface Treatment: Phosphate and chromate Thread Series Designator: Unf Specification Or Standard:
Phosphate and chromate <b>Thread Series Designator:</b> Unf <b>Specification Or Standard:</b>
Thread Series Designator: Unf Specification Or Standard:
Unf Specification Or Standard:
Specification Or Standard:
2 type and 10p style
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
А003b0