Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-018-6494

2a	
Fhread Direction:	
Right-hand	
Thread Length:	
Between 0.869 inches and 0.969 inches	
Fastener Length:	
Between 0.969 inches and 1.000 inches	
lead Style:	
Hexagon	
Head Height:	
Between 0.172 inches and 0.190 inches	
Nidth Between Flats:	
Between 0.428 inches and 0.437 inches	
Nasher Quantity:	
nternal Drive Style:	
Slot	
Thread Diameter:	
).250 inches	
Thready Qty Per Inch (tpi):	
20	
Primary Washer Outside Diameter:	
Between 0.460 inches and 0.475 inches	
Primary Washer Style:	
Flat external teeth	
Primary Washer Material Thickness:	
Between 0.023 inches and 0.028 inches	
Naterial:	
Steel comp 1010 or steel comp 1020 or steel comp 1050	
Naterial Specification:	
Sae assn standard all material responses	
Surface Treatment:	
Cadmium or zinc	
Surface Treatment Specification:	
Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z	325, type 1, cl 3 federal specification 2nd treatment response
Thread Series Designator:	
Jnc	
Shelf Life:	
N/a	
Jnit Of Measure:	

## NSN 5305-00-018-6494

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

