NSN 5305-00-019-0575

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-019-0575 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.398 inches and 0.469 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.428 inches and 0.437 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Primary Washer Outside Diameter:** Between 0.460 inches and 0.475 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.023 inches and 0.028 inches Material: Steel comp 1020 or steel comp 1050 **Material Specification:** Sae assn standard all material responses **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-00-019-0575

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0