## NSN 5305-00-019-0798

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-019-0798 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** 0.312 inches **Head Style:** Round **Head Diameter:** Between 0.240 inches and 0.260 inches **Head Height:** Between 0.091 inches and 0.103 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Nonmachine Thread Style: Dog type (type b or c) **Primary Washer Outside Diameter:** Between 0.270 inches and 0.280 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** 0.016 inches Material: Steel comp 1010 or steel comp 1011 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 **Material Specification:** Qq-s-633 federal specification all material responses **Surface Treatment:** Cadmium or zinc **Thread Series Designator:** Unc Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5305-00-019-0798

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0